

4.4. ANCHOR- WINDLASS

CUSTOM BUILT

All anchor-windlasses can be supplied with:

- a pneumatic free-fall with remote-control,
- the drive can be hydraulic-, electric-, electric/hydraulic- and diesel.
- Execution can be with:
 - 1, 2 or more wildcats
 - 1 or more rope-drums
 - 1 or 2 warpingheads

Available models are:

pull force	power	hauling-speed	chain- diameter
500 kg	2,5 kW	10 m/min	⌀12,5 Dam ⌀14 DIN 766 A ⌀13 DIN 766 A
1000 kg	4,0 kW	10 m/min	⌀16 Dam ⌀14 Dam ⌀18 DIN 766 A ⌀16 DIN 766 A
2 ton	5,5 kW	10 m/min	⌀22 Dam ⌀20,5 Dam ⌀19 Dam ⌀17,5 Dam ⌀23 DIN 766 A ⌀20 DIN 766 A
3,5 ton	7,5 – 11 kW	10 m/min	⌀28 Dam ⌀26 Dam ⌀24 Dam ⌀30 DIN 766 A ⌀28 DIN 766 A ⌀26 DIN 766 A
5,5 ton	15 kW	10 m/min	⌀36 Dam ⌀34 Dam ⌀32 Dam ⌀30 Dam ⌀39 DIN 766 A ⌀36 DIN 766 A ⌀33 DIN 766 A
8 ton	22 kW	10 m/min	⌀40 Dam